



Power Team

ACID RINSE



ST-No.	New Item #	Case UPC Mfg. No. 071206	Each UPC Mfg. No. 071206	Case Size	Case Weight	Cases /Pallet
ST-115	#1201150	101150	201157	4 x 1 gallon case	44 pounds	48
ST-116	#1201167	101167	N/A	5 gallon pail	53 pounds	36
ST-117	#1201174	101174	N/A	15 gallon drum	155 pounds	9

Acid blend for daily rinsing pipelines and dairy equipment

- For everyday use in dairy pipeline systems
- Low-foaming blend of phosphoric acid and sulfuric acid
- Keeps milkstone and water deposits in check
- For CIP (clean in place) and manual use

Directions

CIP CLEANING OF PIPELINES, MILKING MACHINES and BULK TANKS

1. Immediately after milking, flush entire system with warm (100°F) water until the water runs clear.
2. Circulate a solution of **SANITERGENT MARK X** or **CHLORINATED PIPELINE DETERGENT** according to their label directions. Hand brush all parts not coming in contact with the solution.
3. After cleaning, rinse thoroughly with water at 120°F and allow to drain.
4. Acid rinse with a solution of **POWER TEAM ACID RINSE** at a rate of 1 ounce per 10 gallons of warm water to prevent milkstone buildup and water spotting. More **POWER TEAM** may be required in hard water and large systems. Twice each week, instead of acid rinsing, rinse with a solution of **POWER TEAM** at a rate of 1 ounce per 2 gallons of 120°-160°F water for 10 minutes for the control of milkstone. Rinse with water and drain.
5. Before reuse, sanitize with a solution **HYPO-CHLOR 6.40** at a rate of 1 ounce per 2 gallons of water (200 ppm) per label directions, or follow local health recommendations. Drain the used solution from the equipment and air dry.

DO NOT RINSE.

For manual cleaning directions, see label.

Chemical Characteristics

Appearance	Red Liquid
Biodegradable	Yes
Corrosive	Yes
DEA-Free	Yes
Fragrance	Acidic
Non-Flammable	Yes
NPE-Free	Yes
NSF Certified	No
pH (concentrate)	<0.5
Phosphorus	Yes
VOC Compliant.....	No

Ingredients

The primary ingredients Power Team Acid Rinse are phosphoric acid, sulfuric acid, and a low foam wetting agent.



STEARNS PACKAGING CORPORATION

4200 Sycamore Avenue (53714) • P.O. Box 3216, Madison, Wisconsin 53704-0216

Telephone: (800) 655-5008 • (608) 246-5150 • Fax: (608) 246-5149

E-mail: stearns@stearnspkg.com • Website: <http://www.stearnspkg.com>